



VISIT [USGME.COM](http://USGME.COM) TO ORDER SAMPLES



### FEATURES & BENEFITS

- Finely granulated surface texture.
- High light reflectance finish (up to LR-0.88) reduces wear and tear on light fixtures and energy use.
- Economical, non-directional pattern reduces installation time and waste.
- Fire resistant system options for life safety and protection of property.
- Available also in ClimaPlus™ formulation for 99% humidity resistance and various plank sizes.
- Available in Pedestal edge for 19mm thickness.

### APPLICATIONS

- Reception
- Commercial stores
- Libraries
- Banks
- Fitness rooms
- Corridors/stairwell
- Waiting area
- Nursery
- Retail stores

Absorption Coefficient	Frequency, Hz	125	250	500	1000	2000	4000	NRC*
	15mm	0.35	0.25	0.15	0.15	0.20	0.30	0.15

\*Calculated to ASTM C 423-01



EN 13964 - 2014 + A1 - 2007



TABLE OF PERFORMANCE

Edge Detail	Item	Size (mm)	NRC	CAC	Light Reflectance	Anti-Mold & Mildew/Sag Resistance	Fire Rating	Recycled Content	VOC Emission	Cost	
SQ 	OLS665	600*600*15	0.15	33	86%			25%	Low	\$	
	OLS225	610*610*15									
	OLC665	600*600*15	0.15	33	88%			39%	Low	\$	
	OLC225	610*610*15									
	OLC625	600*1200*15	0.15	33	88%			39%	Low	\$	
	OLC245	610*1220*15									
	OLX665	600*600*15	0.15	35	86%			56%	Low	\$\$	
	OLX225	610*610*15									
	PLANKS	OLC325	300*1200*15	0.15	33	88%			39%	Low	\$\$\$
		OLC145	310*1220*15								
		OLS669	600*600*19	0.15	37	86%			25%	Low	\$\$\$
		OLS229	610*610*19								
	PLANKS	OLC669	600*600*19	0.15	37	88%			39%	Low	\$\$\$
		OLC229	610*610*19								
OLC359		300*1500*19	0.15	37	88%			39%	Low	\$\$\$\$	
OLC159		310*1520*19									
SLT 	OLSR665	600*600*15	0.15	33	86%			25%	Low	\$	
	OLSR225	610*610*15									
	OLCR665	600*600*15	0.15	33	88%			39%	Low	\$	
	OLCR225	610*610*15									
	PLANKS	OLCR325	300*1200*15	0.15	33	88%			39%	Low	\$\$\$
		OLCR145	310*1220*15								
	OLSR669	600*600*19	0.15	37	86%			25%	Low	\$\$\$	
	OLSR229	610*610*19									
	OLC629	600*1200*19	0.15	37	88%			39%	Low	\$\$\$	
	OLC249	610*1220*19									
	OLCR629	600*1200*19	0.15	37	88%			39%	Low	\$\$\$	
	OLCR245	610*1220*19									
FLB 	OLSRF665	600*600*15	0.15	33	86%			25%	Low	\$	
	OLSRF225	610*610*15									
	OLCRF665	600*600*15	0.15	33	88%			39%	Low	\$	
	OLCRF225	610*610*15									
	PLANKS	OLCRF325	300*1200*15	0.15	33	88%			39%	Low	\$\$\$
		OLCRF145	310*1220*15								
	OLSRF669	600*600*19	0.15	37	86%			25%	Low	\$\$\$	
	OLSRF229	610*610*19									
	OLXR629	600*1200*19	0.15	37	86%			56%	Low	\$\$\$	
	OLXR249	610*1220*19									
OLCRF629	600*1200*19	0.15	37	88%			39%	Low	\$\$\$		
OLCRF249	610*1220*19										
PEDESTAL 	DPIOLCRI669	600*600*19	0.15	37	88%			39%	Low	\$\$\$	
	DPIOLCRI229	610*610*19									
	DP4OLCRI669	600*600*19	0.15	37	88%			39%	Low	\$\$\$	
	DP4OLCRI229	610*610*19									

**High Recycled Content**  
 Classified as containing greater than 50% total recycled content. Total recycled content is based on product composition of postconsumer and preconsumer (postindustrial) recycled content per FTC guidelines.  
**For firechief products.**



OLYMPIA™



EN 13964 - 2014 + A1 - 2007



GRID PROFILE OPTIONS

DX/DXL SQ Edge	DXT SQ Edge	DX/DXL SLT Edge	DXT FLB Edge	DXF FLB Edge	DXT PEDESTAL

SPECIFICATION DETAILS

Olympia™ Acoustical Ceiling meets specifications in accordance with ASTM E1264 and EN13964.

**Materials Classification**

Type: III,  
Form: 2,  
Pattern: E

**Substrate and Surface Finish**

Mineral fiber substrate finished with factory-applied water-based paint

**Thickness**

15mm, 19mm

**Size**

300 x 1200mm, 310 x 1220mm,  
300 x 1500mm, 310 x 1520mm,  
600 x 600mm, 610 x 610mm,  
600 x 1200mm, 610 x 1220mm

**Edge Detail Trim**

Square,  
Reveal [SLT, FLB, Pedestal]

**Weight**

15mm [3.6 kg/m<sup>2</sup>, Regular/ ClimaPlus™],  
15mm [5.1 kg/m<sup>2</sup>, Firecode®],  
19mm [4.5 kg/m<sup>2</sup>, Regular/ ClimaPlus™],  
19mm [6.45 kg/m<sup>2</sup>, Firecode®]

**Noise Reduction Coefficient [NRC]**

[0.15]

**Ceiling Attenuation Class [CAC]**

[35 - 37 dB]

**Humidity Resistance**

Maximum 99% RH / 40°C for ClimaPlus™

**Light Reflectance Coefficient [LR]**

0.86-0.88

**Color**

White similar to RAL 9016

**Surface Burning Characteristics as per ASTM E84**

Class A

**Reaction to Fire as per EN 13501-1**

Euroclass A2-s1, d0

**Fire Rating as per ASTM E119**

2hrs Time-Rated Assembly [J201]

**Thermal Conductivity**

λ = 0.057 W/m<sup>2</sup>K

**Washability / Scrubbability as per ASTM D4828 & D2486**

Exceeds 1000 Wash/Scrub cycles without surface break or the extent of abrasion upon request

**Formaldehyde Classification**

Class E1 as per EN717-1

**Relevant LEED® Credit**

EA Credit 1 | MR Credit 4 | MR Credit 5 |  
MR Credit 6 | IEQ Credit 3 | IEQ Credit 3.2 |  
IEQ Credit 4.6 | IEQ Credit 8.1 | IEQ Credit 9

**Notice:**

As we are involved in constant products development; this document information is subject to change without prior notice. Please always refer to [usgme.com](http://usgme.com) for the updated products information document.

©2021 Factory of USG Middle East LTD. Co. All rights reserved.

